



# STORMSHIELD

NETWORK SECURITY

## STORMSHIELD SN-M-SERIES-720

Supports the development of your business



### Fiber

CONNECTIVITY

### 18 Gbps

FIREWALL  
PERFORMANCE

### 4 Gbps

IPSEC VPN  
PERFORMANCE

### Modularity

CONNECTIONS  
PERFORMANCE



### Support your growth

With its scalable performance and network modularity, the SN-M-Series-720 is perfectly suited to your growth needs.



### Scalability

- 1 platform for 2 products
- 18 Gbps of firewall throughput, scalable to 36 Gbps
- Conversion to SN-M-Series-920 with software option



### Adaptability and modularity

- Copper and fiber interfaces (2.5GbE and 10GbE) and network expansion capabilities
- Service continuity through redundant power supply
- Integration with telecom racks in existing infrastructures



### All-in-one equipment

- VPN IPsec and intrusion prevention
- High availability
- Interactive reports to facilitate risk mitigation



NEXT GENERATION UTM  
& FIREWALL

MEDIUM-SIZE  
ORGANISATIONS

[WWW.STORMSHIELD.COM](http://WWW.STORMSHIELD.COM)

# TECHNICAL SPECIFICATIONS

## PERFORMANCE\*

Firewall throughput (1,518 byte UDP)	18 Gbps
IPS throughput (1,518 byte UDP)	10 Gbps
IPS throughput (1 MB HTTP)	5 Gbps
Antivirus throughput	3 Gbps

## VPN\*

IPSec throughput - AES-GCM	4 Gbps
Max number of IPSec VPN tunnels	1,000
Number of SSL VPN clients in portal mode	300
Number of simultaneous SSL VPN clients	300

## NETWORK CONNECTIVITY

Max number of simultaneous sessions	1,000,000
Number of new sessions/sec.	50,000
Number of main gateways (max)/backup (max)	64/64

## CONNECTIVITY

2.5 Gb copper interfaces	8-16
10 Gb copper interfaces	0-4
1 Gb fiber interfaces	0-8
10 Gb fiber interfaces	2 <sup>1</sup> -6
Optional network extension modules (8 ports 10/100/1000 - 4 ports 10 Gb copper - 8 ports 1 Gb fiber - 4 ports 10 Gb fiber)	1

## SYSTEM

Number of filtering rules (recommended / specific config)	8,192 / 32,768
Max number of static routes	5,120
Max number of dynamic routes	10,000

## REDUNDANCY

High availability (active/passive)	✓
Redundant power supply*	Double integrated non-hot swappable

## HARDWARE

Storage	✓
Log Partition	> 200 Gb
MTBF at 25 °C (years)	21.4
Size	1U - 19"
Height x Width x Depth (mm)	44.45 x 440 x 343
Weight	4.93 kg (10.86 lbs)
Power supply (AC)	100-240 V 60-50 Hz 3-1.5 A
Consumption	230 V 50 Hz 37 W 0.23 A
Fans	2
Noise level	62 dbA
Thermal dissipation (max, BTU/h)	270
Operating temperature	0° to 40 °C (32° to 104 °F)
Relative humidity when operating (without condensation)	0% to 90% at 40°C
Storage temperature	-30° to 65 °C (-22° to 149 °F)
Relative humidity for storage (without condensation)	5% to 95% at 60 °C

## CERTIFICATIONS

Compliance	CE/FCC/CB
------------	-----------

<sup>1</sup> Requires transceivers

\* Performance is measured in a laboratory and under conditions ideal for version 4.x. Results may vary according to the test conditions and the software version.

# FEATURES

## USAGE CONTROL

Firewall/IPS/IDS mode - Identity-based firewall - Application detection and management - Microsoft Services Firewall - Industrial firewall/IPS/IDS - Industrial application control - Detection and control of the use of mobile terminals - Application inventory (option) - Vulnerability detection (option) - Geolocation (countries, continents) - Dynamic host reputation - URL filtering (embedded database or cloud mode) - Transparent authentication (Active Directory SSO Agent, SSL, SPNEGO) - Multi-user authentication in cookie mode (Citrix-TSE) - Guest and sponsorship mode authentication, webservices.

## PROTECTION FROM THREATS

Intrusion detection and prevention - Protocol auto-detection and compliance check - Application inspection - Protection from denial of service (DoS) attacks - Protection from SQL injections - Protection from Cross-Site Scripting (XSS) - Protection from malicious Web2.0 code and scripts - Trojan detection - Detection of interactive connections (Botnets, Command&Control) - Protection from data evasion - Advanced fragmentation management - Automatic quarantining in the event of an attack - Antispam and antiphishing: reputation-based analysis, heuristic engine - Embedded antivirus (HTTP, SMTP, POP3, FTP) - SSL decryption and inspection - VoIP protection (SIP) - Collaborative security: IP Reputation, Cloud-based Sandbox hosted in Europe (option).

## CONFIDENTIALITY OF EXCHANGES

Site-to-site or nomad IPSec VPN - Remote SSL VPN access in multi-OS tunnel mode (Windows, Android, iOS, etc.) - SSL VPN agent with automatic configuration (Windows) - IPSec VPN support for Android/iPhone.

## NETWORK - INTEGRATION

IPv6 - NAT, PAT, transparent (bridge)/routed/hybrid modes - Dynamic routing (RIP, OSPF, BGP) - Multiple link management (balancing, failover) - Multi-level internal or external PKI management - Multi-domain directories (including internal LDAP) - Explicit proxy - Policy-based routing (PBR) - Quality of Service management - DHCP client/relay/server - NTP client - DNS proxy-cache - HTTP proxy - LACP management - Spanning-tree management (RSTP/MSTP) - SD-WAN, Multifactor Authentication (MFA).

## MANAGEMENT

Web-based management interface with privacy mode (GDPR compliant) - Object-oriented security policy - Contextual security policy - Real-time configuration support - Firewall rule usage counters - Multiple installation wizards - Global/local security policy - Embedded log reporting and analysis tools - Interactive and customisable reports - Support for multiple syslog servers: UDP/TCP/TLS - SNMP v1, v2c, v3 agent - IPFIX - Automated configuration backup - Open API - Script recording.

.....  
**Non-contractual document.** The features mentioned are for version 4.x.